PRODUCT INFORMATION

SCOUT

814SUAC200P60 95A

EAN 4031582419658
Order number 00864562

BETTER MOBILITY. BETTER LIFE.



Image may differ from the original product

PERFORMANCE

Roll performance	● ● ● ○ ○
Movement noise	● ● ● ○ ○
Attrition	● ● ● ● ○
Corrosion resistance	● ● ● ● ●

CORE ATTRIBUTES

Product name	Scout
Housing type	Swivel castor with spring loaded directional lock
Standard	similar EN12532 - Transport Equipment
Load capacity at 4 km/h	350 kg
Load capacity Static	700 kg
Temperature range (Minimum)	-40 °C
Temperature range (Maximum)	80 °C
Overall height	245 mm
Overall width	74 mm
Overall weight	3.024 kg

WHEEL

Body material	Polyamide
Web Wheel Dropdown	Polyurethane, injected, Precision ball bearing, stainless (U A C)
Tread material	Polyurethane, injected
Bearing	Precision ball bearing, stainless
Wheel color	Slate grey (RAL7015)
Threadguards	With threadguard
Diameter	200 mm
Tread width	40 mm
Body width	40 mm
Hardness of tread (A)	92 Shore A
Hardness of tread (D)	42 Shore D

HOUSING

Material	Stainless steel, heavy
Fork shape	Angular
Swivel bearing	Precision ball bearing
Colour	Stainless steel
Offset	50 mm
Swivel radius	150 mm
Swivel interference	300 mm
Dome diameter	68 mm
Stainless	✓

FITTING

Fitting type	Rectangular plate
Web Fitting Dropdown	Rectangular plate 130 Millimetre (P60)
Plate length	130 mm
Plate width	74 mm
Plate hole length (Maximum)	50 mm
Plate hole width (Maximum)	110 mm
Plate hole diameter	10.5 mm

© Copyright 2025 TENTE International GmbH

SCOUT

814SUAC200P60 95A

EAN 4031582419658
Order number 00864562

BETTER MOBILITY. BETTER LIFE.

TECHNICAL DRAWINGS





