INTEGRAL

2044UAP150R36-28S45 D RAL9002 4xM8

EAN 4031582472622

Swivel castor with central, total lock and central directional lock, frame made of pressed steel, precision ball bearing in swivel head and wheel, housing cover made of synthetic plastics, stem with cam hole for profile bars, short version. Wheel centre made of Polyamide, Tread: Polyurethane, precision ball bearing
Hint: TÜV Süd certified product.

BETTER MOBILITY. BETTER LIFE.




Picture may differ from original product

Technical Data

Wheel diameter	150 mm
Width of Tread	32 mm
Castor width	62 mm
Bolt-Ø	28 mm
Bolt length	88 mm
Offset	40 mm
Swivel Interference	230 mm
Overall height	183 mm
Temperature	- 30 / + 80 °C
Standard	EN 12531 (load capacity)
Weight	1.09 kg
Swivel Radius	115 mm
Hardness of tread	Shore D 42
Load capacity	150 kg
Load capacity (static)	300 kg

Dimensions



Advantages at a glance

Roll performance	● ● ● ○ ○
Movement noise	● ● ● ○ ○
Attrition	● ● ● ● ○
Corrosion resistance	● ● ● ○ ○

© Copyright 2020 TENTE International **www.tente.com** 29/04/2020

INTEGRAL

2044UAP150R36-28S45 D RAL9002 4xM8

EAN 4031582472622

Structure & Mounting

